

GRAS 43AF-S1

1" 6cc Coupler Kit According to IEC 60318-3 with 26AB
Preamplifier



Connection: 200 V/LEMO
Volume: 6 cc Dyn range: 14 dB(A) to 146 dB
ANSI: S3.7
IEC: 60318-3

The GRAS 43AF-S1 Artificial Ear is a complete test jig for acoustically testing telephone handsets and earphones and complies with ANSI S 3.7 – 1995 – American National Standard for Testing Earphones.:

The GRAS 43AF-S1 Artificial Ear is a complete test jig for acoustically testing telephone handsets and earphones and complies with ANSI S 3.7 – 1995 – American National Standard for Testing Earphones.:



| | | |
|--|-----------------|------------------------|
| Theoretical dynamic range lower limit with GRAS preamplifier | dB(A) | 14 |
| Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ±14 V power supply | dB | 134 |
| Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ±60 V power supply | dB | 146 |
| Set sensitivity @ 250 Hz (±2 dB) | mV/Pa | 50 |
| Set sensitivity @ 250 Hz (±2 dB) | dB re 1V/Pa | -26 |
| Coupler volume | mm ³ | 6 ccm |
| Temperature range, operation | °C / °F | -30 to 60 / -22 to 140 |
| Temperature coefficient @250 Hz | dB/°C / dB/°F | -0.01 / -0.006 |
| Humidity range non condensing | % RH | 0 to 80 |
| ANSI standard | | S3.7 |
| IEC standard | | 60318-3 (former 60303) |
| ITU-T recommendations | | P.380 |
| CE/RoHS compliant/WEEE registered | | Yes/Yes/Yes |
| Connector type | | 3 m 7-pin LEMO |
| Weight | g / oz | 1.75 / 61.729 |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

| | |
|-----------------------------|-----------------------------------|
| GRAS RA0075 | NBS 9A Coupler |
| GRAS RA0076 | Thread Adapter |
| GRAS 40EN | 1" Microphone |
| GRAS 26AB | ¼" Preamplifier |
| GRAS RA0052 | Test Jig |
| GRAS AA0008 | 3 m LEMO 7-pin - LEMO 7-pin Cable |

Optional

| | |
|---------------------------|--------------|
| GRAS 12AK | Power Module |
| GRAS 42AA | Pistonphone |

Miscellaneous

| | |
|-----------------------------|-----------------------------------|
| GRAS RA0196 | High-tension springs (set of two) |
|-----------------------------|-----------------------------------|

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA
GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK
GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA
GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand