

GRAS 42AE

Low Frequency Calibrator



Sound pressure level: 140 dB
Freq range: 0.01 to 250 Hz

The GRAS 42AE Low-Frequency Calibrator permits microphone calibration at frequencies down to 0.01 Hz for both front and rear-vented microphones. It produces a constant sound pressure level down to very low frequencies.

Typical applications and use

- Low-frequency pressure response measurements
- Low-frequency phase response measurements
- Comparative measurements
- Single and dual-channel measurements

Design

The two-port configuration allows the actual sound pressure in the coupler to be monitored by a reference microphone simultaneously with the microphone under test.

The built-in DC-coupled power amplifier enables the calibration to be used for swept-sine, broadband and step function investigations.

The calibrator can be used for both rear-vented and side-vented microphones. In the case of rear-vented microphones, the 42AE can seal the microphone from the preamplifier to obtain the response of the microphone independent of other leaks.

The calibration of microphones in the frequency range below 50 Hz requires a special apparatus that exposes the complete microphone to the pressure variations of the calibration signal, and not just the microphone diaphragm alone. The air equalization system of a microphone is important for determining the low-frequency response, together with the amplifier of the electronic system.

Air equalization must be fast enough to compensate for changes in altitude and barometric conditions, and slow enough not to affect the response of the microphone at the lowest frequencies. Most measurement microphones will be adjusted to a lower limiting frequency of 1 – 3 Hz. But 0.1 Hz is not unusual for infra-sound measurements as well as for airbag testing.

Around the body of the 42AE, which houses the coupler and all its pre-assembled contents, are input and output sockets as well as a green LED.

The accessories included with the 42AE are, more or less, common to all measurements setups. The manual describes a series of configurations and measurement setups and specifies in detail what items are required in each case.

The dual channel Power Module 12AR is recommended because it can be used at frequencies down to 0.05 Hz.



Frequency range (± 1 dB)	Hz	0.01 - 100
Frequency range (± 2 dB)	Hz	0.01 - 250
Sound pressure level	dB	140
Input signal, max.	Vrms	0.7
ANSI standard		S1.10
Weight	g / oz	1.6k / 56.438

Calibration signal 1 mV/Pa (140 dB max)

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK
GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA
GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK
GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA
GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand