



W.

Freq range: ANSI: S.1.40, S.1.43, S.1.11, S.3.6 IEC: 60318-1 & -2 The GRAS Audiometer Calibration Systems are configured to meet the requirements of modern audiometer calibration. They are easy and fast to set up and control, and can be upgraded as your calibration needs change.

GRAS Sound & Vibration Skovlytoften 33, 2840 Holte, Denmark **www.grasacoustics.com**



Technology

Page: 2

The GRAS 90AB Basic Audiometer Calibration system is configured for the stationary calibration lab and will also calibrate supra- and circum-aural audiometric earphones like TDH-39, HDA 200, HDA280 and HDA 300.

The configuration includes a GRAS Audiometer Calibration Analyzer, two complete sets of standardized ear simulators and a coupler platform.

Typical Applications and Use

Typical users are:

- Owners of Audiometers
 - Hospitals, ENT-department (ordinary and military)
 - Hearing clinics
 - Hearing aid fitters / dispensers
- Calibration service providers
 - Test houses / Certification labs
 - On-site calibration providers

Typical applications and uses:

- Calibration of supra- and circum-aural and insert earphones
- Free-field calibration and audiometric booth verification
- Modular artificial ear systems according to standards
- Dedicated audiometer calibration analyzer





Page: 3

| ANSI standard | S1.40, S1.43, S1.11, S3.6 |
|---------------|---------------------------|
| IEC standard | 60318-1 & 60318-2 |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



Ordering Info

Page: 4

Included

| GRAS 43AF-S4 | Artificial Ear w/NMS 9A 6cc coupler |
|--------------|---|
| GRAS 40AG | ½″ Ext. Polarized Pressure Microphone, High Frequency |
| GRAS HW1001 | Audiometer Calibration Analyzer |
| GRAS RA0039 | IEC 60318 Ear Simulator |
| GRAS EL0001 | Battery Alkaline LR6-AA 1.5 V (4 pcs incl.) |
| GRAS LI0039 | Manual |

Optional

| GRAS OP0001 | Insert Earphone Option (IEC60318-5 2cc Reference Coupler RA0113 for 1" Microphone) |
|-------------|---|
| GRAS 0P0002 | Free-field Calibration Option (Free-field microphone 46AF, 10 m LEMO cable, tripod adapter and tri- pod) |
| GRAS OP0003 | System Verification Option (Sound calibrator 42AB and force gauge) |
| GRAS KM0078 | Suitcase |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

USA

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

GRAS SOUND & VIBRATION 9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

.

GRAS SOUND & VIBRATION Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

CHIN

GRAS SOUND & VIBRATION Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require. GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com



grasacoustics.com