

GRAS 43AD-S1

CCP Ear Simulator Kit According to ITU-T Rec. P57 Type 1



Connection: 0 V/CCP

Volume: Complex

Dyn range: 25 dB(A) to 150 dB

ANSI: S3.7

IEC: 60318-1

The GRAS 43AD-S1 Artificial Ear with TEDS is a complete assembly for acoustical measurements on acoustical transmitters and loudspeakers. It can be integrated with a telephone test head or permanently installed on a production test line.

The GRAS 43AD-S1 is a complete assembly for acoustical measurements on acoustical transmitters and loudspeakers in accordance with:

- IEC 60318-1 & -2 Electroacoustics – Simulators of human head and ear – Part 1: Ear simulator for the calibration of supra-aural earphones, 1998-07
- ITU-T Recommendation P.57 (08/96) Series P: Telephone transmission quality, Objective measuring apparatus: Artificial ears.

It can be integrated with a telephone test head or permanently installed on a production test line.

The 43AD-S1 comprises:

- IEC 60318 [GRAS RA0039 Ear Simulator](#)
- [GRAS 40AO ½" Pressure Microphone](#)
- [GRAS 26CA ¼" Preamplifier](#)
- Snap coupling GR0332 and RA0523
- Mounting plates for circum-aural and supra-aural headphones

An externally polarized version is available, [GRAS 43AD](#).

TEDS Compatibility

43AD-S1 is IEEE 1451.4 TEDS v. 1.0 compliant. If your measurement platform supports Transducer Electronic Data Sheets (TEDS), you will be able to read and write data like properties and calibration data.

| | | |
|---|---------------|------------------------|
| Theoretical dynamic range lower limit with GRAS preamplifier | dB(A) | 25 |
| Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ± 14 V power supply | dB | 150 |
| Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ± 60 V power supply | dB | 164 |
| Set sensitivity @ 250 Hz (± 2 dB) | mV/Pa | 12 |
| Set sensitivity @ 250 Hz (± 2 dB) | dB re 1V/Pa | -38.5 |
| Temperature range, operation | °C / °F | -30 to 60 / -22 to 140 |
| Temperature coefficient @250 Hz | dB/°C / dB/°F | -0.01 / -0.006 |
| Humidity range non condensing | % RH | 0 to 80 |
| ANSI standard | | S3.7 |
| IEC standard | | 60318-1 (former 60318) |
| ITU-T recommendations | | P.57 Type 1 |
| CE/RoHS compliant/WEEE registered | | Yes/Yes/Yes |
| Connector type | | 3 m 7-pin LEMO |
| Weight | g / oz | 1.65 / 58.202 |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

Included

| | |
|-----------------------------|--|
| GRAS RA0039 | IEC 318 Ear Simulator |
| GRAS 40AG | ½" Pressure Microphone, Wide Frequency |
| GRAS 26AK | ½" Preamplifier |
| GRAS AA0034 | 3 m Extension Cable |
| GR0332 | Snap Coupling (female) |
| GR0336 | Snap Coupling (male) |
| GR0339 | for testing earphones fitted with fluid cushions |

Optional

| | |
|---------------------------|--------------|
| GRAS 12AK | Power Module |
| GRAS 42AA | Pistonphone |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more
than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION

Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand