

GRAS 43AF

1" 6cc

IEC 60318-3



200 V/LEMO

6 cc

14 dB(A) - 146 dB

ANSI S3.7

IEC 60318-3

GRAS 43AF

ANSI S 3.7 - 1995 -

GRAS 43AF
1995 -

ANSI S 3.7 -

Specifications

GRAS 43AF 1" 6cc
60318-3

IEC

Page: 3

Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	14
Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ±14 V power supply	dB	134
Theoretical dynamic range upper limit with GRAS preamplifier @ +120 V / ±60 V power supply	dB	146
Set sensitivity @ 250 Hz (±2 dB)	mV/Pa	50
Set sensitivity @ 250 Hz (±2 dB)	dB re 1V/Pa	-26
Coupler volume	mm ³	6 ccm
Temperature range, operation	°C / °F	-30 to 60 / -22 to 140
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01 / -0.006
Humidity range non condensing	% RH	0 to 80
ANSI standard		S3.7
IEC standard		60318-3 (former 60303)
ITU-T recommendations		P.380
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Connector type		3 m 7-pin LEMO
Weight	g / oz	1.75 / 61.729

GRAS Sound & Vibration

□□

GRAS RA0075	NBS 9A
GRAS RA0076	
GRAS 40EN	1
GRAS 26AC	$\frac{1}{4}$
GRAS RA0052	

□□

GRAS 12AK	
GRAS 42AA	

□□

GRAS RA0196	()
-----------------------------	-----

GRAS Sound & Vibration

GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require. GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand