GRAS 50GI-R

CCP





Freq range: IEC 61043 Class 1 Dyn range: 27 dB(A) to 146 dB

Sensitivity: 12.5 mV/pa

50GI-R 61043 IEPE ¼" CCP IEC



Technology

Typical Applications and Uses

- Sound intensity measurements
- Sound source location
- Sound power measurements
- IEC 61043 standard measurements
- Sound source ranking
- · Sound intensity mapping

Design

The probe set includes solid interchangeable spacers for microphone separations from 12 mm to 100 mm so that the probe can cover the frequency range from 50 Hz to 10 kHz.

All components are made specifically for sound intensity applications. Each small ¼" diameter by 40 mm long microphone preamplifier is housed in a robust stainless steel casing, which enables novel probe designs for reducing disturbances to the soundfield otherwise brought about by the effects of shadows and diffraction, and a symmetry which enables reliable calibrations as described in the proposed standard (ISO/DIS 9614-2) for sound power measurements using sound intensity measurements.

The 50GI-R CCP Intensity Probe comprises a 40GK sound Intensity Microphone Pair, two 26CB CCP Microphone Preamplifiers, four solid spacers of various lengths, windscreen, and probe handle with remote control.

The 50GI-R is delivered in a carrying case as a ready-to-use kit, complete with all the above accessories. The microphones are ½" free-field prepolarized microphones with a uniquely-designed pressure equalization system which ensures extremely well defined phase characteristics.

The microphones and preamplifiers are mounted on a swivel head on the telescopic arm of the Remote control handle. To cover the full frequency range from 50 Hz to 10 kHz, the 50GI-R probe is delivered with four solid spacers for spacing the microphones at 12 mm, 25 mm, 50 mm and 100 mm. These spacers can be easily interchanged without dismantling the probe.



Specifications

| Polarization/Connection | | 0 V / CCP |
|-------------------------|--------|-------------------|
| Frequency range (±2 dB) | Hz | IEC 61043 Class 1 |
| Connector type | | 12-pin LEMO |
| Weight | g / oz | 400 / 14.110 |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



Included

| GRAS 40GK | Microphone set |
|---------------|--|
| GRAS 26CB Set | 1/4" CCP Preamplifier |
| | Spacers |
| GRAS RA0003 | Adapter for 1/2" microphone and 1/4" preamplifier |
| GRAS RA0001 | Right-angled (90°) Adapter for 1/2" microphone and 1/4" preamplifier |
| GRAS AA0021 | 5 m cable for Intensity Probe |
| GRAS AC0024 | Adapter Cable for CCP Intensity Probe |
| GRAS AA0084 | Cable, SMB-Microdot, 30 cm (male-male) |
| GRAS KE0132 | Serial to USB Adapter |
| GRAS AI0048S | Probe handle |
| GRAS AI0001 | Windscreen |

Optional

| GRAS 51AB | Phase Calibrator according to IEC 61043 |
|-------------|---|
| GRAS 42AP | Intelligent Pistonphone, Class 0 |
| GRAS RA0024 | Coupler for two-port Calibration |

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION

Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

GRAS

An Axiometrix Solutions Brand

grasacoustics.com