GRAS 45BC-2

KEMAR 2 CCP





CCP 2 ANSI: S3.36, S3.25 IEC: 60318-4 ITU-T Rec. P.57 Type 3.3 based on ITU-T Rec. P.58 45BC-2 TEDS 2-Ch CCP IEC 60318-4

KEMAR 45BC-2

LEMO GRAS 45BC-1 KEMAR 2

LEMO



GRAS 45BC-2 KEMAR 2 CCP

2

Technology

<u>" "</u>

KEMAR Knowles 1972

KEMAR.us ANSI

SZ Z6/ASA58-2012 JEC 60Z18-7:2011 KEMAR

S3.36/ASA58-2012 IEC 60318-7:2011 KEMAR

KEMAR KEMAR GRAS KEMAR 5 6

45BC KEMAR 45BC KEMAR

KEMAR 45BC KEMAR

KEMAR

TEDS □□□

CCP KEMAR IEEE 1451.4 TEDS v. 1.0

TEDS

45BC-2 KEMAR

USB

45BC-2 GRAS 60318-4 RA0045-S1

KB0065/KB0066

GRAS ITU-T P51

1/3 100 dB 20 µPa 100 Hz 16

kHz

60318-4

RA0045-S1

IEC 60318-4 ITU-T P.57

RA0045-S1

KB0065/KB0066 Pinnae

KB0065 KB0066 55 Shore 00 IEC

ITU-T



GRAS 45BC-2 KEMAR 2 CCP

Specifications

Set sensitivity @ 250 Hz (±2 dB) Theoretical dynamic range lower limit with GRAS preamplifier Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ±14 V power supply Theoretical dynamic range upper limit with GRAS CCP preamplifier Resonance frequency Temperature range, operation Temperature range, storage Humidity range non condensing ANSI standard	mV/Pa dB re 1V/Pa dB(A)	12.5 -38.5
Theoretical dynamic range lower limit with GRAS preamplifier Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ±14 V power supply Theoretical dynamic range upper limit with GRAS CCP preamplifier Resonance frequency Temperature range, operation Temperature range, storage Humidity range non condensing	, ,	-38.5
Theoretical dynamic range upper limit with GRAS preamplifier @ +28 V / ±14 V power supply Theoretical dynamic range upper limit with GRAS CCP preamplifier Resonance frequency Temperature range, operation Temperature range, storage Humidity range non condensing	4D(V)	
+28 V / ±14 V power supply Theoretical dynamic range upper limit with GRAS CCP preamplifier Resonance frequency Temperature range, operation Temperature range, storage Humidity range non condensing	UD(A)	25
Resonance frequency Temperature range, operation Temperature range, storage Humidity range non condensing	dB	151
Temperature range, operation Temperature range, storage Humidity range non condensing	dB	146
Temperature range, storage Humidity range non condensing	kHz	13.5
Humidity range non condensing	°C/°F	-30 to 60 / -22 to 140
	°C/°F	-40 to 65 / -40 to 149
ANSI standard	% RH	0 to 95%
7.1.10.1.01.21.11.21.12		S3.36, S3.25
IEC standard		60318-7
ITU-T recommondations		P. 58
Weight	g / oz	11.45 k / 404
MOUTH SIMULATOR		
Output impedance		8
Maximum power, continuous	W	10
Maximum power, pulsed 2 sec.	W	50
Input impedance	k	20
Gain	dB	10
Input signal, max.	Vrms	2
Power supply, external		2

GRAS Sound & Vibration



Ordering info

GRAS 45BC	KEMAR Head & Torso with GRAS mouth simulator, non-configured
GRAS KB0065	KEMAR Large Right Ear 55 Shore 00
GRAS KB0066	KEMAR Large Left Ear 55 Shore 00
GRAS RA0237	Straight Ear Canal Extension Kit for KEMAR (2 pcs)
GRAS RA0045- S1	IEC 60318-4 Ear Simulator, (Prepol.version, 2 pcs)
GRAS 26CS	1/4" CCP Standard Preamplifier with Microdot Connector, Very Short (2 pcs)
<u>GRAS RA0001</u>	Adapter for 1/2" Microphone and 1/4" Preamplifier (2 pcs)
GRAS GR0408	External Ear Canal (2 pcs)
GRAS GR0409	Union Nut (2 pcs)
GRAS AA0018-S	Microdot-BNC Cable, 35 cm (2 pcs)
GRAS AA0035	3 m BNC - BNC Cable (2 pcs)
GRAS 46BD	1/4" CCP Pressure Standard Microphone Set
GRAS AA0070	Microdot-BNC Cable, 3 m

Power Modules for Pre-polarized Ear Simulators and Microphones

GRAS 12AL	1-Channel CCP Power Module with A-weighting filter
GRAS 12AQ	2-Channel Universal Power Module with signal conditioning and PC interface

For Ear Simulator Calibration

GRAS 42AP	Intelligent Pistonphone (250 Hz or 251.2 Hz, 114 dB +/- 0.05 dB)
GRAS 42AA	Pistonphone (250 Hz, 114 dB +/- 0.08 dB)
GRAS RA0157	1/2" Calibration Adapter for KEMAR Pinna

Pinna Simulators



Ordering info

GRAS KB0060	KEMAR Small Right Ear 55 Shore 00
GRAS KB0061	KEMAR Small Left Ear 55 Shore 00
<u>GRAS KB0065</u>	KEMAR Large Right Ear 55 Shore 00
<u>GRAS KB0066</u>	KEMAR Large Left Ear 55 Shore 00
<u>GRAS KB1060</u>	KEMAR Small Right Ear, 35 Shore 00
GRAS KB1061	KEMAR Small Left Ear 35 Shore 00
<u>GRAS KB1065</u>	KEMAR Large Right Ear 35 Shore 00
<u>GRAS KB1066</u>	KEMAR Large Left Ear 35 Shore 00
<u>GRAS KB0090</u>	KEMAR Large Right Ear (VA-Style/SQ) 55 Shore 00
GRAS KB0091	KEMAR Large Left Ear (VA-Style/SQ) 55 Shore 00
<u>GRAS KB1090</u>	KEMAR Large Right Ear (VA-Style) 35 Shore 00
GRAS KB1091	KEMAR Large Left Ear (VA-Style) 35 Shore 00

Ear Mould Simulators

<u>GRAS KB0110</u>	Ear Mould Simulator for 2 mm Inner diameter tubing
GRAS KB0111	Ear Mould Simulator for 3 mm Inner diameter tubing

Ear Canal Extension and Microphone Holder Kits (kits with 2 pcs and O-rings)

GRAS RA0237	Straight Ear Canal Extension Kit for KEMAR
GRAS RA0238	VA-tapered Ear Canal Extension Kit for KEMAR
GRAS RA0239	Ear canal Extension Kit w. silicone lining for KEMAR
GRAS RA0240	Holder for long 1/2" microphone Kit for KEMAR
GRAS RA0241	Holder for short 1/2" microphone Kit for KEMAR
GRAS RA0243	Holder for 1/2" microphone Kit for KEMAR
GRAS RA0244	O-ring kit for KEMAR, 2 pcs.
GRAS RA0249	Straight Ear Canal Extension Kit for KEMAR, made of POM, for binaural hearing aid test
GRAS RA0250	Tapered Ear Canal Extension Kit for KEMAR, made of POM, for binaural hearing aid test



KEMAR Retrofit Kit for Binaural Hearing Aid Test

<u>GRAS RA0251</u>	KEMAR Retrofit Kit for Binaural Hearing Aid Test: The Kit includes Ear Holder Plates, mounting bolts and the RA0249 and RA0250 Ear Canal Extension Kits. Included items are made of POM, Nylon and Teflon.
--------------------	--

Extension Cables

GRAS AA0034	BNC-BNC Cable, 2 m
GRAS AA0035	BNC-BNC Cable, 3 m
GRAS AA0036	BNC-BNC Cable, 5 m
GRAS AA0037	BNC-BNC Cable, 10 m

Flight Case

GRAS KM0094	PELI Case for KEMAR	

Simulation Model of KEMAR

GRAS KB3000	Simulation Model of KEMAR with large pinnae
GRAS KB3001	Simulation Model of KEMAR with small pinnae

Stand for KEMAR

GRAS AL0026	Loudspeaker stand for KEMAR, & 35 mm

Miscellaneous

GRAS KB0000	KEMAR Handbook
GRAS KB0010	T-Shirt for KEMAR

GRAS Sound & Vibration



GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION

9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION

Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION

Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

GRAS

An Axiometrix Solutions Brand

grasacoustics.com