

GRAS 67TS

湍流屏蔽套件



Turb. att.: Up to 25 dB*
Turb. speed: Up to Mach 0.2
Freq. range (turbulence) 500 Hz - 10 kHz*
Acoustic att.: Less than 3 dB
Directivity: ± 60 Deg *Depending on flow-speed

GRAS 67TS 湍流屏蔽套件设计用于在实壁风洞中进行空气声学测试。湍流的流体动力成分被衰减达 25 dB 因此，能以可靠的分辨率识别和诊断感兴趣的声学信号。

Introduction

The GRAS 67TS Turbulence Screen Kit is designed for aeroacoustic testing in solid-walled wind tunnels. By attenuating the hydrodynamic component of turbulence up to as much as 25 dB, the acoustic signals of interest can be identified and diagnosed with a much more reliable resolution. The flush-mount turbulence screen integrates the flush-mount and recessed mounting techniques with a special wire mesh into a single unit, and allows for adaptation of several mounting options.

The kit does not include a microphone set. The [GRAS 67TS-CL-1](#) includes a [GRAS 47BX 1/4" Flush-mount microphone set](#).

A GRAS 1/4" CCP Flush-mount Microphone Set can be attached to the turbulence screen assembly either with a "rubber band" (O-ring) or a holder plate of POM-material. The parts necessary for both methods are part of the GRAS RA0295 Turbulence Screen Accessories for Flush-mount Microphones. This kit must be ordered separately.

A GRAS 1/4" standard microphone set can be attached to the turbulence screen assembly with a straight or an angled holder plate. These are part of the GRAS RA0296 Turbulence Screen Accessories for standard microphone/preamplifier. This kit must be ordered separately.

As "default" the complete assembly will fit in a flat wall with 4 mm thickness. A hole with diameter 44 mm must be provided. It is possible to attach the assembly using glue. For mounting with screws, the 67TS is provided with 4 holes with diameter 3.1 mm. You are always welcome to contact GRAS for advice or regarding customization.

Polarization/Connection		0 V / CCP
IEC 61094-4 Compliance		WS3P

Included items

GRAS 67TS	Turbulence Screen Kit
---------------------------	-----------------------

Accessories

GRAS RA0295	Turbulence Screen Kit Accessories for Flush-mount Microphone
GRAS RA0296	Turbulence Screen Kit Accessories for for standard microphone/preamplifier

GRAS Sound & Vibration reserves the right to change specifications and accessories without notice.

GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0)7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION
Room 502, Building T1,
No.1398 Ali Center
Shenchang Road,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 400-888-9826
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones to industries where acoustic measuring accuracy and repeatability is of utmost importance in R&D, QA and production. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, and consumer electronics. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect and trust.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.GRASacoustics.com

www.GRASacoustics.com

GRAS
An Axiometrix Solutions Brand