

GRAS 50AI-LP

1/2" CCP



IEC 61043 Class 1
25 dB(A) - 152 dB
12.5 mV/Pa

GRAS 50AI-LP 1/2" CCP
ICP

◆◆◆◆

-
-
-

◆◆

GRAS 50AI-LP 1/2" CCP

ICP

IEC 61043 1 1/4" CCP

50AI-LP 12mm 50mm 80 Hz 10 kHz

1/4" 40mm
ISO/DIS 9614-2

½"

50AI-LP

50AI-LP GRAS

◆◆

GRAS

◆◆

GRAS 50AI-LP 5

GRAS

◆◆◆◆◆

GRAS

Polarization/Connection		0 V / CCP
Frequency range (± 2 dB)	Hz	Ref. IEC 61043 Class 1
Dynamic range lower limit (microphone thermal noise)	dB(A)	25
Dynamic range upper limit	dB	152
Set sensitivity @ 250 Hz (± 2 dB)	mV/Pa	12.5
Microphone venting		Rear
Temperature range, operation	°C / °F	5 to 40 / 41 to 104
Temperature coefficient @250 Hz	dB/°C / dB/°F	-0.01
Humidity range non condensing	% RH	0 - 100
Humidity coefficient @250 Hz	dB/% RH	-0.001
Influence of axial vibration @1 m/s ²	dB re 20 μ Pa	66
Connector type		12-pin LEMO
CE/RoHS compliant/WEEE registered		Yes/Yes/Yes
Weight	g / oz	400 / 14.110

GRAS Sound & Vibration



GRAS RA0213	Rugged Probe Head
GRAS 40GK-S1	1/2" Intensity Microphone Set
<u>GRAS RA0001</u>	Right-angled (90°) Adapter for 1/2" microphone and 1/4" preamplifier
GRAS GR0040	Holder for spacer
GRAS RA0264	Spacer, 50 mm
GRAS RA0265	Spacer, 25 mm
GRAS RA0266	Spacer, 12 mm
<u>GRAS 26CC</u> Set	1/4" CCP Preamplifier set
GRAS AA0021	5 m Extension Cable, 5 m, 12 pin LEMO male - male
GRAS AC0022	Adapter cable, 12-pin LEMO to 2 x BNC + USB Adapter
GRAS AA0068	2 x SMB to Microdot cable, 25 cm (male-male)
GRAS AI0048S	Probe handle
<u>GRAS AM0376</u>	Windscreen



GRAS AA0010-S1	3 m LEMO 12-pin - Lemo 12-pin, Cable for Intensity Probe
<u>GRAS AA0010</u>	10 m LEMO 12-pin - Lemo 12-pin, Cable for Intensity Probe
<u>GRAS 51AB</u>	Intensity Calibrator
<u>GRAS 42AP</u>	Pistonphone with built-in barometer and thermometer (recommended)
<u>GRAS 42AA</u>	Pistonphone
<u>GRAS RA0024</u>	Two-port Calibration Coupler (for GRAS 42AP or 42AA Pistonphones)
<u>GRAS 51AC</u>	Sound Intensity Calibration Kit for 50AI-LP

GRAS Sound & Vibration

GRAS Worldwide

Subsidiaries and distributors in more than 40 countries

HEAD OFFICE, DENMARK

GRAS SOUND & VIBRATION
Skovlytoften 33
2840 Holte
Denmark
Tel: +45 4566 4046
www.GRASacoustics.com
gras@grasacoustics.com

USA

GRAS SOUND & VIBRATION
9290 SW Nimbus Avenue
Beaverton, OR 97008
Tel: 503-627-0832
Toll Free: 800-231-7350
www.GRASacoustics.com
sales-usa@grasacoustics.com

UK

GRAS SOUND & VIBRATION
Unit 115, Gibson House,
Ermine Business Park, Huntingdon,
Cambridgeshire, PE29 6XU
Tel: +44 (0) 7762 584 202
www.GRASacoustics.com
sales-uk@grasacoustics.com

CHINA

GRAS SOUND & VIBRATION
Room 315, RuiBo Center(T1)
Lane683, Shenhong Rd,
Minhang District,
Shanghai, China, 201107
Tel: +86 21 64203370
www.GRASacoustics.cn
cnsales@grasacoustics.com



About GRAS Sound & Vibration

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require. GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

grasacoustics.com

GRAS
An Axiometrix Solutions Brand