# **GRAS 45BC-14**

2 CCP KEMAR





CCP ANSI: S3.36, S3.25 IEC: 60318-4, 60318-7 ITU-T Rec. P.57 Type 3.3 ITU-T Rec. P.58

45BC-14 KEMAR TEDS 45BC-14

LEMO GRAS 45BC-13



KEMAR Knowles 1972 ( KEMAR.us ) ANSI S3.36/ASA58-2012 IEC 60318-7:2011	35 Shore 00 KEMAR
KEMAR KEMAR GRAS	KEPIM
	supra-aural circumaural
45BC KEMAR 45BC KEMAR KEMAR 45BC KEMAR KEMAR	KEMAR DUT
TEDS [][]  CCP KEMAR IEEE 1451.4 TEDS v. 1.0  TEDS	
45BC-14 KEMAR	
USB	20 kHz
45BC-14 GRAS RA0402 KB5000/KB50001	45BC-14 KEMAR
GRAS ITU-T P51 1/3 100 dB 20 μPa 100 Hz 16 kHz	COCO KEMAR 2
RA0402	KEMAR 5 6
RA0402 IEC60318-4 10 kHz 13.5 kHz 20 kHz IEC60318-4 IEC60318-4 10 kHz 20 kHz ±2.2 dB THD	
IEC 60318-4 ITU-T P.57	
GRAS 40A0 1/2	
RA0402	



## Specifications

Set sensitivity @ 250 Hz (±2 dB)  Set sensitivity @ 250 Hz (±2 dB)  Theoretical dynamic range lower limit with GRAS preamplifier  Theoretical dynamic range upper limit with GRAS CCP preamplifier  Resonance frequency  RHz  Table  Temperature range, operation  C / °F  Temperature range, storage  C / °F  Temperature range, storage  C / °F  Temperature range, storage  RNSI standard  S3.36, S3.25  S3.25  S4.			
Theoretical dynamic range lower limit with GRAS preamplifier  Theoretical dynamic range upper limit with GRAS CCP preamplifier  Resonance frequency  Resonance frequency  Resonance frequency  Resonance frequency  Resonance frequency  Resonance frequency  RHz  13.5  Temperature range, operation  C / °F  -30 to 60 / -22 to 140  Temperature range, storage  C / °F  -40 to 65 / -40 to 149  Humidity range non condensing  RH  0 to 95%  ANSI standard  S3.36, S3.25  IEC standard  60318-7  ITU-T recommondations  P. 58  Weight  g / oz  11.45 k / 404  MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  W  10  Maximum power, pulsed 2 sec.  W  50  Input impedance  k  25	Set sensitivity @ 250 Hz (±2 dB)	mV/Pa	12.5
Theoretical dynamic range upper limit with GRAS CCP preamplifier  Resonance frequency  RHz  13.5  Temperature range, operation  °C / °F  -30 to 60 / -22 to 140  Temperature range, storage  °C / °F  -40 to 65 / -40 to 149  Humidity range non condensing  % RH  0 to 95%  ANSI standard  S3.36, S3.25  IEC standard  60318-7  ITU-T recommondations  P. 58  Weight  MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  M  10  Maximum power, pulsed 2 sec.  W  50  Input impedance  k  20	Set sensitivity @ 250 Hz (±2 dB)	dB re 1V/Pa	-38.5
Resonance frequency  KHz  13.5  Temperature range, operation  °C / °F  -30 to 60 / -22 to 140  Temperature range, storage  °C / °F  -40 to 65 / -40 to 149  Humidity range non condensing  % RH  0 to 95%  ANSI standard  S3.36, S3.25  IEC standard  60318-7  ITU-T recommondations  P. 58  Weight  MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  W  10  Maximum power, pulsed 2 sec.  W  50  Input impedance  k  20	Theoretical dynamic range lower limit with GRAS preamplifier	dB(A)	25
Temperature range, operation  °C / °F  -30 to 60 / -22 to 140  Temperature range, storage  °C / °F  -40 to 65 / -40 to 149  Humidity range non condensing  % RH  0 to 95%  ANSI standard  \$3.36, \$3.25  IEC standard  60318-7  ITU-T recommondations  P. 58  Weight  g / oz  11.45 k / 404  MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  W  10  Maximum power, pulsed 2 sec.  Input impedance  k  20	Theoretical dynamic range upper limit with GRAS CCP preamplifier	dB	150
Temperature range, storage  C / °F  -40 to 65 / -40 to 149  Humidity range non condensing  % RH  0 to 95%  ANSI standard  S3.36, S3.25  IEC standard  60318-7  ITU-T recommondations  P. 58  Weight  MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  M  10  Maximum power, pulsed 2 sec.  Input impedance  k  20	Resonance frequency	kHz	13.5
Humidity range non condensing % RH 0 to 95%  ANSI standard S3.36, S3.25  IEC standard 60318-7  ITU-T recommondations P. 58  Weight g / oz 11.45 k / 404  MOUTH SIMULATOR .  Output impedance 8  Maximum power, continuous W 10  Maximum power, pulsed 2 sec. W 50  Input impedance k 20	Temperature range, operation	°C/°F	-30 to 60 / -22 to 140
ANSI standard S3.36, S3.25  IEC standard 60318-7  ITU-T recommondations P. 58  Weight g / oz 11.45 k / 404  MOUTH SIMULATOR .  Output impedance 8  Maximum power, continuous W 10  Maximum power, pulsed 2 sec. W 50  Input impedance k 20	Temperature range, storage	°C/°F	-40 to 65 / -40 to 149
IEC standard         60318-7           ITU-T recommondations         P. 58           Weight         g / oz         11.45 k / 404           MOUTH SIMULATOR         .           Output impedance         8           Maximum power, continuous         W         10           Maximum power, pulsed 2 sec.         W         50           Input impedance         k         20	Humidity range non condensing	% RH	0 to 95%
ITU-T recommondations  Weight  g / oz  11.45 k / 404  MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  W  10  Maximum power, pulsed 2 sec.  W  50  Input impedance  k  20	ANSI standard		S3.36, S3.25
Weight g / oz 11.45 k / 404  MOUTH SIMULATOR .  Output impedance 8  Maximum power, continuous W 10  Maximum power, pulsed 2 sec. W 50  Input impedance k 20	IEC standard		60318-7
MOUTH SIMULATOR  Output impedance  8  Maximum power, continuous  W 10  Maximum power, pulsed 2 sec.  W 50  Input impedance  k 20	ITU-T recommondations		P. 58
Output impedance 8  Maximum power, continuous W 10  Maximum power, pulsed 2 sec. W 50  Input impedance k 20	Weight	g / oz	11.45 k / 404
Maximum power, continuous  W 10  Maximum power, pulsed 2 sec.  W 50  Input impedance  k 20	MOUTH SIMULATOR		
Maximum power, pulsed 2 sec.  W 50  Input impedance  k 20	Output impedance		8
Input impedance k 20	Maximum power, continuous	W	10
	Maximum power, pulsed 2 sec.	W	50
Gain dB 10	Input impedance	k	20
	Gain	dB	10
Input signal, max. Vrms 2	Input signal, max.	Vrms	2
Power supply, external Vdc 24	Power supply, external	Vdc	24



## Ordering info

## 

GRAS 45BC	KEMAR Head & Torso with GRAS mouth simulator, non-configured
<u>GRAS KB5000</u>	KEMAR Large Right Anthropometric Pinna 35 Shore 00
<u>GRAS KB5001</u>	KEMAR Large Left Anthropometric Pinna 35 Shore 00
GRAS GR0408	External Ear Canal (for calibration, 2 pcs)
GRAS GR0409	Union Nut (for GR0408, 2 pcs)
GRAS GR1874	Ear Simulator Holder (2 pcs)
GRAS RA0402	High Resolution Ear Simulator, (Prepol.version, 2 pcs)
GRAS 26CS	1/4" CCP Standard Preamplifier with Microdot Connector, Very Short (2 pcs)
<u>GRAS RA0001</u>	Right Angled Adapter for 1/2" Microphone and 1/4" Preamplifier (2 pcs)
<u>GRAS AA0018-S</u>	Microdot-BNC Cable, 35 cm (2 pcs)
<u>GRAS AA0035</u>	3 m BNC - BNC Cable (2 pcs)
GRAS 46BD	1/4" CCP Pressure Standard Microphone Set
GRAS AA0070	Microdot-BNC Cable, 3 m

## 

## **Power Modules for Pre-polarized Ear Simulators and Microphones**

GRAS 12AL	1-Channel CCP Power Module with A-weighting filter
GRAS 12AQ	2-Channel Universal Power Module with signal conditioning and PC interface

## **For Ear Simulator Calibration**

GRAS 42AP	Intelligent Pistonphone (250 Hz or 251.2 Hz, 114 dB +/- 0.05 dB)
GRAS 42AA	Pistonphone (250 Hz, 114 dB +/- 0.08 dB)



## **Pinna Simulators**

GRAS KB5000	Large Right Anthropometric Pinna 35 Shore 00
<u>GRAS KB5001</u>	Large Left Anthropometric Pinnar 35 Shore 00
GRAS KB0060	KEMAR Small Right Ear 55 Shore 00
GRAS KB0061	KEMAR Small Left Ear 55 Shore 00
GRAS KB0065	KEMAR Large Right Ear 55 Shore 00
GRAS KB0066	KEMAR Large Left Ear 55 Shore 00
GRAS KB1060	KEMAR Small Right Ear, 35 Shore 00
GRAS KB1061	KEMAR Small Left Ear 35 Shore 00
GRAS KB1065	KEMAR Large Right Ear 35 Shore 00
GRAS KB1066	KEMAR Large Left Ear 35 Shore 00
<u>GRAS KB0090</u>	KEMAR Large Right Ear (VA-Style/SQ) 55 Shore 00
<u>GRAS KB0091</u>	KEMAR Large Left Ear (VA-Style/SQ) 55 Shore 00
<u>GRAS KB1090</u>	KEMAR Large Right Ear (VA-Style) 35 Shore 00
GRAS KB1091	KEMAR Large Left Ear (VA-Style) 35 Shore 00

## **Ear Mould Simulators**

GRAS KB0110	Ear Mould Simulator for 2 mm inner diameter tubing
<u>GRAS KB0111</u>	Ear Mould Simulator for 3 mm inner diameter tubing

## Ear Canal Extension and Microphone Holder Kits (kits with 2 pcs and O-rings)

GRAS RA0237	Straight Ear Canal Extension Kit for KEMAR
GRAS RA0238	VA-tapered Ear Canal Extension Kit for KEMAR
GRAS RA0239	Ear Canal Extension Kit w. silicone lining for KEMAR
GRAS RA0240	Holder for long 1/2" microphone Kit for KEMAR



GRAS RA0241	Holder for short 1/2" microphone Kit for KEMAR
GRAS RA0243	Holder for 1/4" microphone Kit for KEMAR
GRAS RA0244	O-ring kit for KEMAR, 2 pcs.
GRAS RA0249	Straight Ear Canal Extension Kit for KEMAR,made of POM, for binaural hearing aid test
GRAS RA0250	Tapered Ear Canal Extension Kit for KEMAR,made of POM, for binaural hearing aid test

## **KEMAR Retrofit Kit for Binaural Hearing Aid Test**

<u>GRAS RA0251</u>	KEMAR Retrofit Kit for Binaural Hearing Aid Test. The Kit includes Ear Holder Plates, mounting bolts and the RA0249 and RA0250 Ear Canal Extension Kits. Included items are made of POM, Nylon and Teflon.
--------------------	--

## **Extension Cables**

GRAS AA0034	BNC-BNC Cable, 2 m
GRAS AA0035	BNC-BNC Cable, 3 m
GRAS AA0036	BNC-BNC Cable, 5 m
GRAS AA0037	BNC-BNC Cable, 10 m

## **Flight Case**

GRAS KM0094	PELI Case for KEMAR

## **Simulation Model of 45BB KEMAR**

GRAS KB3000	3D Simulation Model of KEMAR with large pinnae, stp file
GRAS KB3001	3D Simulation Model of KEMAR with small pinnae, stp file



## Ordering info

GRAS KB3002

3D Simulation Model of KEMAR with anthropometric pinnae, stp file

## **Stand for KEMAR**

***************************************	
GRAS AL0026	Loudspeaker stand for KEMAR, & 35 mm

## **Miscellaneous**

GRAS KB0000	KEMAR Handbook
GRAS KB0010	T-Shirt for KEMAR

**GRAS Sound & Vibration** 



## **GRAS** Worldwide

Subsidiaries and distributors in more than 40 countries

### **HEAD OFFICE, DENMARK**

### **GRAS SOUND & VIBRATION**

Skovlytoften 33 2840 Holte Denmark Tel: +45 4566 4046 www.GRASacoustics.com gras@grasacoustics.com

#### USA

### **GRAS SOUND & VIBRATION**

9290 SW Nimbus Avenue Beaverton, OR 97008 Tel: 503-627-0832 Toll Free: 800-231-7350 www.GRASacoustics.com sales-usa@grasacoustics.com

#### UK

### **GRAS SOUND & VIBRATION**

Unit 115, Gibson House, Ermine Business Park, Huntingdon, Cambridgeshire, PE29 6XU Tel: +44 (0) 7762 584 202 www.GRASacoustics.com sales-uk@grasacoustics.com

#### CHINA

### **GRAS SOUND & VIBRATION**

Room 315, RuiBo Center(T1) Lane683, Shenhong Rd, Minhang District, Shanghai, China, 201107 Tel: +86 21 64203370 www.GRASacoustics.cn cnsales@grasacoustics.com



### **About GRAS Sound & Vibration**

GRAS is a worldwide leader in the sound and vibration industry. We develop and manufacture state-of-the-art measurement microphones and related equipment for industries where acoustic measuring accuracy and repeatability are of the utmost importance. This includes applications and solutions for customers within the fields of aerospace, automotive, audiology, consumer electronics and other highly demanding industries. GRAS microphones are designed to live up to the high quality, durability and accuracy that our customers have come to expect, trust and require.

GRAS Sound & Vibration is represented through subsidiaries and distributors in more than 40 countries and is part of Axiometrix Solutions, a leading test solutions provider comprised of globally recognized measurement brands. Read more at www.grasacoustics.com

GRAS

An Axiometrix Solutions Brand

grasacoustics.com